



# **poolwater balancer**

**Active Ingredient:** Calcium Chloride Compound......100%

- Rapidly Increases Total Hardness
- Helps Prevent Corrosion or Etching of Pools

**4**<sup>lb</sup>

## **KEEP OUT OF REACH OF CHILDREN** CAUTION

See first aid and additional precautions on back panel.

# **GREEN LINE DOWN INDICATES BACK OF POUCH • GREEN LINE DOWN INDICATES BACK OF POUCH • GREEN LINE DOWN INDIC**

This is a dry granular product that increases the total hardness in pool water to the recommended range.

DIRECTIONS

Test for calcium hardness with a reliable test kit. The desired range for calcium hardness is as follows:

Vinyl Pools	200-300 ppm
Tile and Exposed Aggregate Pools	200-400 ppm
Marcite, Fiberglass or Painted Pools	250-400 ppm

If the calcium hardness tests less than the desired range, add this product according to the chart below. Place this product into a plastic bucket already filled with swimming pool water. Do this in a ration of up to 2 pounds of product per approximate 5-gallon bucket of water. Slowly pour this solution around the perimeter of the swimming pool while the circulating system is operating. In a 10,000 gallon pool, do not add more than 10 pounds of this product per 2 hour period.

#### HOW TO INCREASE CALCIUM HARDNESS IN YOUR POOL

DESIRED INCREASE IN PPM	GALLONS IN POOL		
	5,000	10,000	20,000
10 ppm	7.2 oz.	14.4 oz.	1.8 lbs.
20 ppm	14.4 oz.	1.8 lbs.	3.6 lbs.
30 ppm	1.35 lbs.	2.7 lbs.	5.4 lbs.
40 ppm	1.8 lbs.	3.6 lbs.	7.2 lbs.
60 ppm	2.7 lbs.	5.4 lbs.	10.8 lbs.
80 ppm	3.6 lbs.	7.2 lbs.	14.4 lbs.
100 ppm	4.5 lbs.	9 lbs.	18 lbs.

### **PRECAUTIONARY STATEMENTS**

**CAUTION:** Product generates heat when combined with water. Avoid contact with eyes and prolonged contact with skin. Do not mix with other chemicals.

#### **FIRST AID**

IF IN EYES: Immediately flush eyes with large amounts of water. Seek medical help if irritation persists.

IF ON SKIN: Wash affected area with soap and water.

IF SWALLOWED: Get medical attention.

IF INHALED: Remove to fresh air.

#### **STORAGE AND DISPOSAL:**

Store closed container in a cool dry, well ventilated place. When container is empty, rinse thoroughly with water, wrap securely in newspaper and place in trash collection.

**Distributed By:** Suncoast Chemicals Company 14480 62nd Street No. Clearwater, FL 33760 In Case of Emergency Call: 1-800-255-3924 MADE IN CHINA



