

Pool Mate

Metal Out

Stain and Mineral Inhibitor

Super Strength

Super-concentrated formula helps prevent stains and discoloration from iron, copper, magnesium and other minerals.

**KEEP OUT OF REACH OF CHILDREN
WARNING**

See first aid and additional precautions on back panel.
Read all directions carefully before use.

1-2550 L1117PH

1 qt

GENERAL INFORMATION

This product helps prevent discoloration of pool water due to iron, calcium, manganese, copper and other metals and minerals which may be present in the water supply. This product is an excellent general purpose sequestrant which helps protect plumbing and pool walls from rust, stain and scale. It should be used for all pool openings and closings, and throughout the season as needed.

DIRECTIONS FOR USE

Read entire label and use strictly in accordance with precautionary statements and directions.

For initial filling of pool, if iron or other metallic contaminants are suspected, add one quart of Metal Out for each 10,000 gallons of pool water. Add Metal Out while the pool is being filled and before chlorine is added.

To correct an existing colored water problem (due to the presence of minerals in the pool water), first close the pool to all swimmers. Leave the filter pump running. Stop chlorinating the pool and allow the chlorine level to drop to zero. Lower the pH of the pool water to 6.8 with pH Lower (lowering the pH will redissolve the metallic impurities). Add one quart of Metal Out per 10,000 gallons of water and allow the pool water to circulate overnight, or until the water is clear. Readjust the pH of the pool water between 7.2 to 7.8 with pH Rise. Begin normal chlorination and pool operation. Swimming may resume when chlorine residual is 1.0 to 3.0 ppm.

To make up for loss of Metal Out due to backwashing and/or splash-out, add one quart of Metal Out for each 20,000 gallons of pool water once each month.

CAUTION

Avoid contact with skin, eyes, or clothing. In case of skin contact wash thoroughly with water. In case of eye contact, immediately flush with water for at least 15 minutes. Seek medical attention.

NOTICE

Manufacturer's and seller's guarantees shall be limited to the terms of the label. Neither shall be held responsible for any personal injury, property damage or other loss resulting from the handling, storage and use of this product not in strict accordance with directions on the label.

In Case of Emergency, Call 1-800-255-3924

Rev No. 1117
103-025113P12
998-PM1200G01



32oz.—
30 —
28 —
26 —
24 —
22 —
20 —
18 —
16 —
14 —
12 —
10 —
8 —
6 —
4 —
2oz.—

(These gradations are approximate)